



Toll Free 866 – 558 – 3369 • Fax 866 – 558 – 2010

quote@warmyourfloor.com

www.WarmYourFloor.com

May we offer a ProMelt™ Outdoor Snow Melting Quotation?

We prefer requests for Snow Melting systems are submitted in writing and Faxed 1-866-558-2010 or Emailed to quote@warmyourfloor.com but you may call in – Please have the following Information available so we can quote you promptly & accurately. **ProMelt Mats & Cables** are available in over 60 standard sizes. Please let us recommend the right solution for your project.

Project Name & Address: _____ Project City & State: _____

Contact Name _____ Email: _____ Phone _____

Are you the : Contractor < OR > HomeOwner Fax _____

Heated Area SF: #1 _____ Dimensions: _____ X _____ Area 2 _____ Dimensions _____ X _____ (Send a sketch?)

Any Steps? No YES Number of steps _____ Width= _____ Depth= _____ Rise= _____
Stairs require a little extra footage. You need a minimum number of runs per tread (we recommend 4 runs per 11-12" tread)

Power Source – Distance from end of heated area: _____ Feet (ProMelt Leads are 20 Ft Standard)
(They can be factory special ordered longer @ \$9.75/Ft or we recommend using a Junction box as needed)

Power For your system: 240 120 208 220 277 (Single Phase ONLY available)

240v is recommended for areas over 53 Sq Ft – Most homes have 240v available – please verify.
(@ 240v 50 Watts/SF requires 0.22 amps per SF) So 200 Sq Ft in concrete requires 44 amps @ 240v
Customer is responsible to choose the correct breaker, wire type & size to Meet NEC, & all code requirements.

Snow/Ice Melting systems will be installed in a: Heavy Snow Area (50w) Medium Snow area (38w)

Choose your type of installation (must be installed in Sand under pavers, Mortar, Asphalt, or Smooth **or** Stamped Concrete. Our Heating cables **CANNOT** be installed in Gravel, Soil, etc.

- In Concrete (inside a New Pour - top 2") attached to reinforcing mesh or rebar with cable ties)
- On top of concrete covered with thickset mortar & Stone/Tile Pavers in mortar / on concrete
(we recommend the overall thickness of stone & mortar on top of cables to be 2 - 2.5" max)
- Pavers in Sand Asphalt (38 watts/SF Limit) Other Surface _____

For Walkways, driveways or other square or rectangular areas we recommend the **ProMelt Mats**; they install easily since the heating elements are spaced perfectly on the reinforced tape grid. If you have an irregular shaped or small area, consider the **ProMelt Cables**.

Warm Your Floor will return a quotation within 1 – 2 business days after receiving a completed form.

ProMelt™ is manufactured in the **USA** by Watts Radiant, the leader in Radiant Heating technology

- Safety Listed by ETL for NORMALLY WET ENVIRONMENTS To Underwriters' Laboratories standards
- World-Class Dual Heating Element Cable using top quality materials
- Over 60 Standard size options available from Stock
- Available in 50 watts/SF (recommended) or 38 watts/SF options in 4 voltage choices
- ProMelt's SINGLE point connection means you do not need to return to the beginning of your run.